

Dialogic Compatibility Chart

As of 08/30/06

Dialogic Voice Board	Tel. Lines	Slot Type & Board Length		Windows Operating System					Dialogic Drivers				
		ISA	PCI	2000 Pro	XP Home	XP Pro	Server 2000	Server 2003	5.0	5.01	5.1.1	6.0	
Model	#												
Proline/2V	2	8"		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
D/21D	4	13"		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
D/41D	4	13"		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
D/41H	4	7"		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
D/41ESC	4	13"		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
D/160SC-LS	16	13"		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
D/240SC-T1	24	13"		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
D/480SC-2T1	48	13"		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
D/4PCI	4		7"	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
D/4PCI-U	4		7"	Yes	Yes	Yes	Yes	Yes			Yes	with Feature Pack 1	Yes
D/4PCI-UF	4		7"			Yes		Yes			Yes	with Feature Pack 1	Yes
D/41E-PCI	4		13"	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
D/41JCT-LS	4		13"	Yes	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes
D/120JCT-LS	12		13"	Yes	Yes	Yes	Yes	Yes		Yes	Yes	Yes	Yes
D/120JCT-LSU	12		13"	Yes	Yes	Yes	Yes	Yes			Yes	with Feature Pack 1	Yes
D/240PCI-T1	24		13"	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	
D/240JCT-T1	24		13"	Yes	Yes	Yes	Yes	Yes			Yes	Yes	Yes
D/240JCT-T1 R2U	12		13"	Yes	Yes	Yes	Yes	Yes			Yes	with Feature Pack 1	Yes
D/480JCT-2T1	48		13"	Yes	Yes	Yes	Yes	Yes			Yes	Yes	Yes
D/480JCT-2T1 R2U	48		13"	Yes	Yes	Yes	Yes	Yes			Yes	with Feature Pack 1	Yes

Notes:

Some ISA & PCI boards can be mixed in the same computer.

"U" and "R2U" PCI boards cannot usually be mixed with "non-U" PCI boards.